



ARC200C / 250C

Cellulosic machine



Features

- INVERTER IGBT
- Available for cellulosic electrode welding
- Portable with light weight.
- Energy saving with excellent dynamic characteristics and high efficiency.
- Stable arc, molten pool easy to control.
- Adjustable arc-force guarantee good performance in long cable welding.
- Applicable to aerial work, field work, indoor and outdoor decoration, etc.

Specifications

Standard

- Built-in Hot Start
- Arc-force knob
- O.H.indicator
- Digital display meter

Optional

- Lift-arc TIG
- VRD & VRD indicator

Accessories

Standard

- 2pcs quick plugs

Optional

- 300A Earth Clamp+16mm²3m cable+quick plug
- 200A Electrode holder+16mm²3m cable+quick plug
- 300A Earth Clamp+25mm²3m cable+quick plug
- 300A Electrode holder+25mm²3m cable+quick plug



	ARC200C Z247	ARC250C Z231
Input power source	1~AC230V±15% 50/60Hz	
Input current(A)	42.8	57
Rated input power capacity(KVA)	9.4	12.3
Output current range(A)	20-200	20-250
Arc force range(A)	-----	0-100
No-load voltage(V)	78	78
Rated duty cycle(%) @40°C	30	60
Efficiency(%)	85	85
Power factor(cosΦ)	0.7	0.7
Protection class	IP21S	IP21S
Insulation class	F	F
Dimensions(mm)	375X290X135	410X152X235
Weight(Kg)	6.7	9