



TIG180 / 200



Accessories

Standard

- 1pc 4m WP-26K-E TIG torch
- 1pc 300A Earth Clamp+16mm²3m cable+quick plug
- 1pc quick plug DKJ35-50



Features

- INVERTER IGBT
- Easy arc ignition with High Frequency.
- Good Arc-stiffness and concentrated heat.
- Stable arc without spatter and good shaping.
- Weld with materials such as steel, stainless steel, titanium, copper, nickel and their alloys.
- Application in vessel, bike, decoration, outdoor advertising, etc.

Specifications

Standard

- HF
- MMA
- Pre-flow
- Down slope
- Built-in Hot Start
- Built-in Arc-force
- O.H.indicator
- 2T/4T

Optional

- Digital display meter
- Dual voltage, AC115/230V
- VRD
- Digital display meter

	TIG180 W206	TIG200 W207
Input power source	1~AC230V ±15% 50/60Hz	
Rated input current(A)	26	31
Rated input power capacity(KVA)	6	7.1
TIG Output current range(A)	10-180	10-200
MMA Output current range(A)	10-160	10-180
Post-flow time(S)	0-15	0-15
Down slope(S)	0-10	0-10
Arc starting	HF	HF
No-load voltage(V)	60	60
Rated duty cycle(%) @40°C	35	35
Efficiency(%)	85	85
Power factor(cosΦ)	0.7	0.7
Protection class	IP21S	IP21S
Insulation class	F	F
Dimensions(mm)	365x135x277	365x135x277
Weight(Kg)	5.9	6.1