




TIG180P / 200P

Digital



Accessories

Standard

- 1pc 4m WP-26K-E TIG torch
- 1pc 300A Earth Clamp+16mm²3m cable+quick plug
- 1pc quick plug DKJ35-50



Features

- INVERTER IGBT
- Digital control, MCU technology, automatic parameter saving.
- Good Arc-stiffness and concentrated heat.
- Stable arc without spatter, good shaping and less deformation.
- Excellent performance with Pulse TIG, special for thin material welding.
- Weld with materials such as steel, stainless steel, titanium, copper, nickel and their alloys.
- Application in vessel, bike, decoration, outdoor advertising, etc.

Specifications

Standard

- HF TIG
- Anti-stick
- Built-in Hot Start
- Built-in Arc-force
- 2T/4T/Spot
- O.H.indicator
- Digital display meter
- Automatic saving parameter

Optional

- VRD
- Pedal remote control
- Current-controlling torch

	TIG180P W211	TIG200P W212
Input power source	1~AC230V ±15% 50/60Hz	
Rated input current(A)	31	36
Rated input power capacity(KVA)	7.1	8.2
TIG Output current range(A)	10-180	10-200
MMA Output current range(A)	10-160	10-180
Pre/Post-flow time(S)	0-15	0-15
Up/Down slope(S)	0-10	0-10
Arc starting	HF	HF
No-load voltage(V)	60	60
Rated duty cycle(%) @40°C	35	35
Efficiency(%)	85	85
Power factor(cosΦ)	0.7	0.7
Protection class	IP21S	IP21S
Insulation class	F	F
Dimensions(mm)	365×135×277	365×135×277
Weight(Kg)	5.9	6.1