

MPI 220P

Issued October 2011 • Index No. DCM/9.5 UK

**MIG/Stick/TIG (Multiprocess)
Arc Welding Power Source**



Quick Specs



Industrial Applications

Light Fabrication
Maintenance and Repair
Auto Body
Farm/Home

Processes

MIG (GMAW)
Pulsed MIG (GMAW-P)
Stick (SMAW)
TIG (GTAW)
Flux Cored (FCAW)

Input Power Rated Output

230 VAC, 50/60 Hz, Single-Phase

MIG: 110 Amps at 17.5 VDC, 100% Duty Cycle
Stick: 100 Amps at 24 VDC, 100% Duty Cycle
TIG: 100 Amps at 14 VDC, 100% Duty Cycle

Amp/Volt Range


MIG: 20–200 A, 15–24 V
Stick: 5–200 A, 20.2–28 V
TIG: 5–200 A, 10–18 V

The Power of Blue.®

Portability is number one when you have to go to the job — because it can't come to you. The MPI 220P contains all you need to MIG weld in one small lightweight package. With the flip of a switch, all processes are available to meet the application at hand.

Large graphical display guides user through process and parameter setup with ease and high visibility.

Full weld process capability. MIG/MAG, Pulse, Stick, and TIG are available to meet the demand of current applications.



Durable cast aluminum feedhead incorporates dual-groove quick-change drive roll and spring-loaded tension arm with calibrated tension knob, all designed to make set up easier and faster.

Thermal overload protection shuts down unit and activates **over temperature light** if airflow is blocked or duty cycle is exceeded. Automatically resets when fault is corrected and unit cools.

New!



Easy access to output studs provides **convenient polarity changeover** when changing from solid or flux cored wires.

Synergic welding mode offers the simplicity of single knob control. The machine will select the correct voltage and amperage based on the wire feed speed (WFS) set by the operator.
Note: Complete material library to select from for the targeted market segment.

Adjustable Hot Start™ for Stick arc starts. Adjust the optimal start current for the application. The current automatically increases the output amperage at the start of a weld.

Built-in upslope/downslope function for TIG helps provide better arc starts and reduces craters.

Built-in run-in/crater/burnback function for MIG helps provide better arc starts and reduces craters.

Adjustable preflow and postflow gives operator better control of the gas parameters affecting weld zone.

Selectable trigger configuration allows the operator to choose standard or 2T trigger method.

Excellent arc characteristics! The MPI 220P offers positive arc starts and an extremely stable arc with minimal spatter on both mixed gases and straight CO₂.

TRUE BLUE
3YR. WARRANTY

Warranted for 3 years, parts and labour.



ITW Welding Products BV – Netherlands

Edisonstraat 10
P.O. Box 1551
NL-3261 LD Oud-Beijerland,
Netherlands
TEL: +31 (0) 186 641 444
FAX: +31 (0) 186 640 880

ITW Welding Products – Italy S.r.l.

Via Privata Iseo 6/e
20098 San Giuliano M.se
Milano – Italy
TEL.: +39 02 982901
FAX: +39 02 98281552
Email: itw@itw-welding.it

International Headquarters Miller Electric Mfg. Co.

An Illinois Tool Works Company
1635 W. Spencer Street
Appleton, WI 54914 USA
TEL.: +1 920 735 4554
FAX: +1 920 735 4125
www.millerwelds.com

Specifications (Subject to change without notice.)



Model	Input Power	Welding Mode	Rated Output (Duty Cycle)			Max. Open-Circuit Voltage	Amperage/Voltage Range DC	IP Rating	Dimensions	Weight
			100%	60%	35%					
MPi 220P	230 VAC, 50/60 Hz, Single-phase	MIG	110 A 17.5 V	140 A 21.0 V	180 A 23.0 V	35 V	2–200 A 15–24 V	IP22S	L: 548 mm (21.6 in) W: 237 mm (9.3 in) H: 365 mm (14.4 in)	16 kg (35 lb)
		Stick	100 A 24.0 V	130 A 25.2 V	170 A 26.8 V	65 V	5–200 A 20.2–28 V			
		TIG	100 A 14.0 V	130 A 15.2 V	180 A 17.2 V	65 V	5–200 A 10–18 V			

Drive Roll Kits

Drive Roll and Wire Guide Kits for MPi 220P

Base selection of drive rolls upon the following recommended usages:

1. V-Grooved rolls for hard wire.
2. U-Grooved rolls for soft and soft-shelled cored wires.
3. U-Cogged rolls for extremely soft-shelled wires (usually hard-surfacing types).
4. V-Knurled rolls for hard-shelled cored wires.

Wire Size	Drive Roll	Type	Wire Guide Inlet
0.6/0.8 mm (.023/.030 in)*	156 053 051	V	156 090 026
0.8/1.0 mm (.030/.035 in)*	156 053 109	V	156 090 026
1.0/1.2 mm (.035/.045 in)*	156 053 052	V	156 090 026
0.8/1.0 mm (.030/.035 in)**	156 053 053	U	156 090 026
1.2/1.6 mm (.045/.065 in)**	156 053 054	U	156 090 026
1.0/1.2 mm (.035/.045 in)*	156 053 110	V-K	156 090 026

*Available in steel, 30 mm diameter. **Available in nylon, 30 mm diameter.

Ordering Information

Power Source and Options	Stock No.	Description	Qty.	Price
MPi 220P	#059 016 014	230 VAC, 50/60 Hz, single-phase. Includes work clamp		
Accessories				
TIG Torch	WTC9AA4AG CS130AGA4CG-I	125 Amps DC, 100 Amps AC, 60% duty cycle 130 Amps DC, 100 Amps AC, 60% duty cycle		
MIG/MAG Torch	Q2010A08DE	200 Amp Q-Gun with 3 m (10 ft) cable		

Date: _____ Total Quoted Price: _____



Distributed by: